

92-600

Disposable Nitrile Glove with Enhanced Chemical Splash Protection

An unparalleled combination of chemical splash protection, comfort and durability

- World leader: TouchNTuff[®] 92-600 gloves are the world's leading disposable gloves for chemical splash protection
- Superior protection: Made with TNT™
 Chemical Splash Resistance Technology, these gloves effectively safeguard hands from exposure to harmful chemicals
- Elevated comfort: Super soft nitrile provides a comfortable feel during extended wear
- Robust durability: EN388 certified, meeting level 1 abrasion to prevent ripping and tearing during heavy-duty work
- Prevents surface defects: Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes



Industries

- Life Sciences
- Food Processing
- Automotive
- Machinery and Equipment
- Chemical
- Agriculture
- Utilities
- Warehousing

Recommended For

- Transferring liquids and solids
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling



TECHNICAL DATA SHEET

	Product Information		
Material	Nitrile		
External Glove Surface	Smooth		
Audit Standards	ISO 9001		
Product Certification	Category III, EN 388:2016 1XXXX, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 18889:2019, ISO 9001, UKCA, DOSH-SIRIM certified		
Packaging Overview	XS*-XL: 100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case XXL*: 90 gloves per dispenser, 10 dispensers per case, 900 gloves per case *Size XS and XXL are not available in China and Brazil		
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.		
Country Of Origin	Malaysia, Sri Lanka, Thailand		
Product Segmentation	Robust		
Antistatic	Yes EN1149		
Silicone Free	Yes		
Vulcanization Chemical Accelerators	 Zinc Dibutyldithiocarbamate (ZDBC) Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions. 		

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	240 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5 A	ASTM D5151,EN 455-1	
Palm Thickness (mm/mils)	0.125/ 4.9		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.14/ 5.5		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 24	≥ 25	ASTM D412 & D573
Elongation at Break (%)	≥ 600	≥ 525	ASTM D412
Force at break (N)	≥ 10	≥ 10	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	92600060	92600070	92600080	92600090	92600100	92600110

Performance Standards and Regulatory Compliance















For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia

Russia Ansell PYC Ten. +7 495 258 13 16 **Technology**



Ansell, $^{\textcircled{8}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{9}}$ 2025 Ansell Limited. All Rights Reserved.

