

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PS26 - Side Shields Safety Glasses

Collection: Eye Protection

Range: PPE

Materials: Polycarbonate, Rubber

Inner Pack: 12 Outer Carton: 120

Product information

Modern full frame style with integrated side shields for excellent lateral protection. Light brown lens protects from blue light helping to prevent eye strain and discomfort when being exposed extensively to sources of blue light such as screens or artificial light.



PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 166 (1 FT) EN 170 (2C-1.2 (clear)) EN 170 (2C-1.4 (light brown)) ANSI/ISEA Z87 +



Features

- · Stylish full frame model
- Integrated side shields for extra protection
- Blue light blocking properties in light brown lens
- Light brown lens helps to reduce eye strain
- Soft arms tips for ultra comfort
- Moulded nose piece for universal fit
- 99% UV protection
- Anti-fog coating for additional comfort to the wearer
- · Anti-scratch coating for added durability
- · CE certified
- UKCA marked



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PS26 - Side Shields Safety Glasses Commodity Code: 9004901000

Test House

SGS FIMKO Ltd (Notified Body No.: NB: 0598)

Takomotie 8 , Finland

Contact: sgs.fimko@sgs.com Cert No: 0598/PPE/23/3113

SGS United Kingdom Limited (Notified Body No.: AB: 0120)

Rossmore Business Park

CH65 3EN, UK

Cert No: 0120/PPE/230507

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
PS26CLR	Clear	58.0	36.0	37.0	0.0400	0.0773	5036108422074	15036108908094